
Stream: Internet Engineering Task Force (IETF)
RFC: [8748](#)
Category: Standards Track
Published: March 2020
ISSN: 2070-1721
Authors: R. Carney G. Brown J. Frakes
GoDaddy Inc. CentralNic Group plc

RFC 8748

Registry Fee Extension for the Extensible Provisioning Protocol (EPP)

Abstract

Given the expansion of the DNS namespace and the proliferation of novel business models, it is desirable to provide a method for Extensible Provisioning Protocol (EPP) clients to query EPP servers for the fees and credits associated with various billable transactions and provide expected fees and credits for certain commands and objects. This document describes an EPP extension mapping for registry fees.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc8748>.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction
 - 1.1. Conventions Used in This Document
2. Migrating to Newer Versions of This Extension
3. Extension Elements
 - 3.1. Client Commands
 - 3.2. Currency Codes
 - 3.3. Validity Periods
 - 3.4. Fees and Credits
 - 3.4.1. Refunds
 - 3.4.2. Grace Periods
 - 3.4.3. Correlation between Refundability and Grace Periods
 - 3.4.4. Applicability
 - 3.5. Account Balance
 - 3.6. Credit Limit
 - 3.7. Classification of Objects
 - 3.8. "Phase" and "Subphase" Attributes
 - 3.9. Reason
4. Server Handling of Fee Information
5. EPP Command Mapping
 - 5.1. EPP Query Commands
 - 5.1.1. EPP <check> Command
 - 5.1.2. EPP Transfer Query Command
 - 5.2. EPP Transform Commands
 - 5.2.1. EPP <create> Command
 - 5.2.2. EPP <delete> Command
 - 5.2.3. EPP <renew> Command

[5.2.4. EPP <transfer> Command](#)

[5.2.5. EPP <update> Command](#)

[6. Formal Syntax](#)

[6.1. Fee Extension Schema](#)

[7. Security Considerations](#)

[8. IANA Considerations](#)

[8.1. XML Namespace](#)

[8.2. EPP Extension Registry](#)

[9. References](#)

[9.1. Normative References](#)

[9.2. Informative References](#)

[Acknowledgements](#)

[Authors' Addresses](#)

1. Introduction

Historically, domain name registries have applied a simple fee structure for billable transactions, namely a basic unit price applied to domain <create>, <renew>, <transfer>, and Redemption Grace Period (RGP) [RFC3915] restore commands. Given the relatively small number of EPP servers to which EPP clients have been required to connect, it has generally been the case that client operators have been able to obtain details of these fees out of band by contacting the server operators.

Given the expansion of the DNS namespace and the proliferation of novel business models, it is desirable to provide a method for EPP clients to query EPP servers for the fees and credits associated with various billable transactions and certain commands and specific objects.

This document describes an extension mapping for version 1.0 of the Extensible Provisioning Protocol (EPP) [RFC5730]. This EPP mapping provides a mechanism by which EPP clients may query the fees and credits associated with various billable transactions and obtain their current account balance.

1.1. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

XML is case sensitive. Unless stated otherwise, the XML specifications and examples provided in this document **MUST** be interpreted in the character case presented in order to develop a conforming implementation.

"fee" is used as an abbreviation for "urn:ietf:params:xml:ns:epp:fee-1.0". The XML namespace prefix "fee" is used, but implementations **MUST NOT** depend on it and instead employ a proper namespace-aware XML parser and serializer to interpret and output the XML documents.

In the examples, "C:" represents lines sent by a protocol client, and "S:" represents lines returned by a protocol server. Indentation and white space in the examples are provided only to illustrate element relationships and are not a required feature of this protocol.

2. Migrating to Newer Versions of This Extension

Servers that implement this extension **SHOULD** provide a way for clients to progressively update their implementations when a new version of the extension is deployed.

Servers **SHOULD** (for a temporary migration period) provide support for older versions of the extension in parallel to the newest version and allow clients to select their preferred version via the <svcExtension> element of the <login> command.

If a client requests multiple versions of the extension at login, then, when preparing responses to commands that do not include extension elements, the server **SHOULD** only include extension elements in the namespace of the newest version of the extension requested by the client.

When preparing responses to commands that do include extension elements, the server **SHOULD** only include extension elements for the extension versions present in the command.

3. Extension Elements

3.1. Client Commands

The <fee:command> element is used in the EPP <check> command to determine the fee that is applicable to the given command.

The "name" attribute of the <fee:command> is used to define which transform fees the client is requesting information about. The possible values for the "name" attribute are:

- "create", indicating a <create> command as defined in [RFC5730].

- "delete", indicating a <delete> command as defined in [RFC5730].
- "renew", indicating a <renew> command as defined in [RFC5730].
- "update", indicating a <update> command as defined in [RFC5730].
- "transfer", indicating a <transfer> command as defined in [RFC5730].
- If the server supports registry grace period mapping [RFC3915], then the server **MUST** also support the "restore" value as defined in [RFC3915].
- "custom", indicating a custom command that **MUST** set the "customName" attribute with a custom command name. The possible set of custom command name values is dictated by the server policy.

The <fee:command> element **MAY** have an **OPTIONAL** "phase" attribute specifying a launch phase as described in [RFC8334]. It may also contain an **OPTIONAL** "subphase" attribute identifying the custom or subphase as described in [RFC8334].

3.2. Currency Codes

The <fee:currency> element is used to indicate the currency in which fees are charged. The value of this element **MUST** be a three-character currency code from [ISO4217_2015].

Note that [ISO4217_2015] provides the special "XXX" code, which **MAY** be used if the server uses a non-currency-based system for assessing fees, such as a system of credits.

The use of <fee:currency> elements in client commands is **OPTIONAL**: if a <fee:currency> element is not present in a command, the server **MUST** determine the currency based on the server default currency or on the client's account settings, which are agreed to by the client and server via an out-of-band channel. However, the <fee:currency> element **MUST** be present in the responses.

Servers **SHOULD NOT** perform a currency conversion if a client uses an incorrect currency code. Servers **SHOULD** return a 2004 "Parameter value range error" instead.

3.3. Validity Periods

When querying for fee information using the <check> command, the <fee:period> element is used to indicate the validity period, which is to be added to extend the registration period of objects by the <create>, <renew>, and <transfer> commands. Validity periods are measured in years or months, with the appropriate units specified using the "unit" attribute. Valid values for the "unit" attribute are "y" for years and "m" for months. This element is derived from the <domain:period> element described in [RFC5731].

The <fee:period> element is **OPTIONAL** in <check> commands; if omitted, the server **MUST** determine the fee(s) using the server default period. The <fee:period> element **MUST** be present in <check> responses.

3.4. Fees and Credits

Servers that implement this extension will include elements in responses that provide information about the fees and/or credits associated with a given billable transaction. A fee will result in subtracting from the Account Balance (described in [Section 3.5](#)), and a credit will result in adding to the Account Balance (described in [Section 3.5](#)).

The `<fee:fee>` and `<fee:credit>` elements are used to provide this information. The presence of a `<fee:fee>` element in a response indicates a debit against the client's account balance; a `<fee:credit>` element indicates a credit. A `<fee:fee>` element **MUST** have a zero or greater (non-negative) value. A `<fee:credit>` element **MUST** have a negative value.

A server **MAY** respond with multiple `<fee:fee>` and `<fee:credit>` elements in the same response. In such cases, the net fee or credit applicable to the transaction is the arithmetic sum of the values of each of the `<fee:fee>` and/or `<fee:credit>` elements. This amount applies to the total additional validity period for the object (where applicable).

The following attributes are defined for the `<fee:fee>` element. These are described in detail below:

description: an **OPTIONAL** attribute that provides a human-readable description of the fee. Servers should provide documentation on the possible values of this attribute and their meanings. An **OPTIONAL** "lang" attribute **MAY** be present, per the language structure in [\[RFC5646\]](#), to identify the language of the returned text and has a default value of "en" (English). If the "description" attribute is not present, the "lang" attribute can be ignored.

refundable: an **OPTIONAL** boolean attribute indicating whether the fee is refundable if the object is deleted.

grace-period: an **OPTIONAL** attribute that provides the time period during which the fee is refundable.

applied: an **OPTIONAL** attribute indicating when the fee will be deducted from the client's account.

The `<fee:credit>` element can take a "description" attribute as described above. An **OPTIONAL** "lang" attribute **MAY** be present to identify the language of the returned text and has a default value of "en" (English).

3.4.1. Refunds

`<fee:fee>` elements **MAY** have an **OPTIONAL** "refundable" attribute that takes a boolean value. Fees may be refunded under certain circumstances, such as when a domain application is rejected (as described in [\[RFC8334\]](#)) or when an object is deleted during the relevant grace period (see [Section 3.4.2](#)).

If the "refundable" attribute is omitted, then clients **SHOULD NOT** make any assumptions about the refundability of the fee.

3.4.2. Grace Periods

[RFC3915] describes a system of "grace periods", which are time periods following a billable transaction during which, if an object is deleted, the client receives a refund.

The "grace-period" attribute **MAY** be used to indicate the relevant grace period for a fee. If a server implements the registry grace period extension [RFC3915], it **MUST** specify the grace period for all relevant transactions.

If the "grace-period" attribute is omitted, then clients **SHOULD NOT** make any assumptions about the grace period of the fee.

3.4.3. Correlation between Refundability and Grace Periods

If a <fee:fee> element has a "grace-period" attribute, then it **MUST** also be refundable, and the "refundable" attribute **MUST** be true. If the "refundable" attribute of a <fee:fee> element is false, then it **MUST NOT** have a "grace-period" attribute.

3.4.4. Applicability

Fees may be applied immediately upon receipt of a command from a client or may only be applied once an out-of-band process (such as the processing of applications at the end of a launch phase) has taken place.

The "applied" attribute of the <fee:fee> element allows servers to indicate whether a fee will be applied immediately or whether it will be applied at some point in the future. This attribute takes two possible values: "immediate" or "delayed".

3.5. Account Balance

The <fee:balance> element is an **OPTIONAL** element that **MAY** be included in server responses to transform commands. If present, it can be used by the client to determine the remaining credit at the server.

Whether or not the <fee:balance> is included in responses is a matter of server policy. However, if a server chooses to offer support for this element, it **MUST** be included in responses to all "transform" or billable commands (e.g., <create>, <renew>, <update>, <delete>, <transfer op="request">).

The value of the <fee:balance> **MAY** be negative. A negative balance indicates that the server has extended a line of credit to the client (see [Section 3.6](#)).

If a server includes a <fee:balance> element in response to transform commands, the value of the element **MUST** reflect the client's account balance after any fees or credits associated with that command have been applied. If the "applied" attribute of the <fee:fee> element is "delayed", then the <fee:balance> **MUST** reflect the client's account balance without any fees or credits associated with that command.

3.6. Credit Limit

As described above, if a server returns a response containing a `<fee:balance>` with a negative value, then the server has extended a line of credit to the client. A server **MAY** also include in responses a `<fee:creditLimit>` element that indicates the maximum credit available to a client. A server **MAY** reject certain transactions if the absolute value of the `<fee:balance>` is equal to or exceeds the value of the `<fee:creditLimit>` element.

Whether or not the `<fee:creditLimit>` is included in responses is a matter of server policy. However, if a server chooses to offer support for this element, it **MUST** be included in responses to all "transform" commands (e.g., `<create>`, `<renew>`, `<update>`, `<delete>`, `<transfer op="request">`).

3.7. Classification of Objects

Objects may be assigned to a particular class, category, or tier, each of which has a particular fee or set of fees associated with it. The `<fee:class>` element, which **MAY** appear in `<check>` and transform responses, is used to indicate the classification of an object.

If a server makes use of this element, it should provide clients with a list of all the values that the element may take via an out-of-band channel. Servers **MUST NOT** use values that do not appear on this list.

Servers that make use of this element **MUST** use a `<fee:class>` element with the value "standard" for all objects that are subject to the standard or default fee.

3.8. "Phase" and "Subphase" Attributes

The `<fee:command>` element has two attributes, "phase" and "subphase", that provide additional information related to a specific launch phase, as described in [\[RFC8334\]](#). These attributes are used as filters that should refine the server processing.

If the client `<fee:command>` contains a server-supported combination of phase/subphase, the server **MUST** return the fee data (including the phase/subphase attribute(s)) for the specific combination.

If the client `<fee:command>` contains no "phase"/"subphase" attributes and the server has only one active phase/subphase combination, the server **MUST** return the data (including the "phase"/"subphase" attribute(s)) of the currently active phase/subphase.

If the client `<fee:command>` contains no phase/subphase attributes and the server has more than one active phase/subphase combination, the server **MUST** respond with a 2003 "Required parameter missing" error.

If the client `<fee:command>` contains no phase/subphase attributes and the server is currently in a "quiet period" (e.g., not accepting registrations or applications), the server **MUST** return data consistent with the default general availability phase (e.g., "open" or "claims"), including the appropriate phase/subphase attribute(s).

If the client `<fee:command>` contains a phase attribute with no subphase and the server has only one active subphase (or no subphase) of this phase, the server **MUST** return the data (including the phase/subphase attribute(s)) of the provided phase and currently active subphase.

If the client `<fee:command>` contains a phase attribute with no subphase and the server has more than one active subphase combination of this phase, the server **MUST** respond with a 2003 "Required parameter missing" error.

If the client `<fee:command>` contains a subphase with no phase attribute, the server **MUST** respond with a 2003 "Required parameter missing" error.

If the client `<fee:command>` contains a phase attribute not defined in [RFC8334] or not supported by the server, the server **MUST** respond with a 2004 "Parameter value range error".

If the client `<fee:command>` contains a subphase attribute (or phase/subphase combination) not supported by the server, the server **MUST** respond with a 2004 "Parameter value range error".

3.9. Reason

The `<fee:reason>` element is used to provide server-specific text in an effort to better explain why a `<check>` command did not complete as the client expected. An **OPTIONAL** "lang" attribute **MAY** be present to identify the language, per the language structure in [RFC5646], of the returned text and has a default value of "en" (English).

The `<fee:reason>` element can be used within the server response `<fee:command>` element or within the `<fee:cd>` element. See [Section 5.1.1](#) for details on the `<fee:cd>` "check data" element.

If the server cannot calculate the relevant fees because the object, command, currency, period, class, or some combination is invalid per server policy, the server has two ways of handling the error processing of `<fee:command>` element(s):

1. Fast-fail: The server, upon error identification, **MAY** stop processing `<fee:command>` elements and return a `<fee:cd>` to the client containing the `<fee:objID>` and a `<fee:reason>` element detailing the reason for failure.

```
S: <fee:cd avail="0">
S:   <fee:objID>example.xyz</fee:objID>
S:   <fee:reason>Only 1 year registration periods are
S:     valid.</fee:reason>
S: </fee:cd>
```

2. Partial-fail: The server, upon error identification, **MAY** continue processing <fee:command> elements and return a <fee:cd> to the client containing the successfully processed <fee:command> elements and failed <fee:command> elements. All returned failed <fee:command> elements **MUST** have a <fee:reason> element detailing the reason for failure, and the server **MAY** additionally include a <fee:reason> element at the <fee:cd> level.

```
S: <fee:cd avail="0">
S:   <fee:objID>example.xyz</fee:objID>
S:   <fee:command name="create">
S:     <fee:period unit="y">2</fee:period>
S:     <fee:reason>Only 1 year registration periods are
S:       valid.</fee:reason>
S:   </fee:command>
S: </fee:cd>
```

In either failure scenario, the server **MUST** set the <fee:cd> "avail" attribute to false (0), and the server **MUST** process all objects in the client request.

4. Server Handling of Fee Information

Depending on the server policy, a client **MAY** be required to include the extension elements described in this document for certain transform commands. Servers must provide clear documentation to clients about the circumstances in which this extension must be used.

The server **MUST** return avail="0" in its response to a <check> command for any object in the <check> command that does not include the <fee:check> extension where the server would fail a domain <create> command when no <fee> extension is provided for that same object.

If a server receives a <check> command from a client that results in no possible fee combination, the server **MUST** set the "avail" attribute of the <fee:cd> element to false (0) and provide a <fee:reason>.

If a server receives a <check> command from a client that results in an ambiguous result (i.e., multiple possible fee combinations), the server **MUST** reject the command with a 2003 "Required parameter missing" error.

If a server receives a command from a client that does not include the fee extension data elements required by the server for that command, then the server **MUST** respond with a 2003 "Required parameter missing" error.

If the total fee provided by the client is less than the server's own calculation of the fee or the server determines the currency is inappropriate for that command, then the server **MUST** reject the command with a 2004 "Parameter value range error".

5. EPP Command Mapping

A detailed description of the EPP syntax and semantics can be found in [\[RFC5730\]](#).

5.1. EPP Query Commands

This extension does not add any elements to the EPP <poll> or <info> commands or responses.

5.1.1. EPP <check> Command

This extension defines a new command called the Fee Check Command that defines additional elements for the EPP <check> command to provide fee information.

The command **MAY** contain an <extension> element, which **MAY** contain a <fee:check> element. The <fee:check> element **MAY** contain one <fee:currency> element and **MUST** contain one or more <fee:command> elements.

The <fee:command> element(s) **MUST** contain a "name" attribute (see [Section 3.1](#)), an **OPTIONAL** "phase" attribute, and an **OPTIONAL** "subphase" attribute (see [Section 3.8](#)). The <fee:command> element(s) **MAY** have the following child elements:

- An **OPTIONAL** <fee:period> element (as described in [Section 3.3](#)).

Example <check> command:

```
C: <?xml version="1.0" encoding="utf-8" standalone="no"?>
C: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
C:   <command>
C:     <check>
C:       <domain:check
C:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
C:         <domain:name>example.com</domain:name>
C:         <domain:name>example.net</domain:name>
C:         <domain:name>example.xyz</domain:name>
C:       </domain:check>
C:     </check>
C:     <extension>
C:       <fee:check xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
C:         <fee:currency>USD</fee:currency>
C:         <fee:command name="create">
C:           <fee:period unit="y">2</fee:period>
C:         </fee:command>
C:         <fee:command name="renew"/>
C:         <fee:command name="transfer"/>
C:         <fee:command name="restore"/>
C:       </fee:check>
C:     </extension>
C:     <cLTRID>ABC-12345</cLTRID>
C:   </command>
C: </epp>
```

When the server receives a <check> command that includes the extension elements described above, its response **MUST** contain an <extension> element, which **MUST** contain a child <fee:chkData> element. The <fee:chkData> element **MUST** contain a <fee:currency> element and a <fee:cd> element for each object referenced in the client <check> command.

Each `<fee:cd>` (check data) element **MUST** contain the following child elements:

- A `<fee:objID>` element, which **MUST** match an element referenced in the client `<check>` command.
- An **OPTIONAL** `<fee:class>` element (as described in [Section 3.7](#)).
- A `<fee:command>` element matching each `<fee:command>` (unless the "avail" attribute of the `<fee:cd>` is false) that appeared in the corresponding `<fee:check>` of the client command. This element **MAY** have the **OPTIONAL** "standard" attribute, with a default value of "0" (or "false"), which indicates whether the fee is the standard or default fee (see [Section 3.7](#)). This element **MAY** have the **OPTIONAL** "phase" and "subphase" attributes, which will match the same attributes in the corresponding `<fee:command>` element of the client command if sent by the client.

The `<fee:cd>` element also has an **OPTIONAL** "avail" attribute, which is a boolean. If the value of this attribute evaluates to false, this indicates that the server cannot calculate the relevant fees because the object, command, currency, period, class, or some combination is invalid per server policy. If "avail" is false, then the `<fee:cd>` or the `<fee:command>` element **MUST** contain a `<fee:reason>` element (as described in [Section 3.9](#)), and the server **MAY** eliminate some or all of the `<fee:command>` element(s).

The `<fee:command>` element(s) **MAY** have the following child elements:

- An **OPTIONAL** `<fee:period>` element (as described in [Section 3.3](#)), which contains the same unit, if present, that appeared in the `<fee:period>` element of the command. If the value of the parent `<fee:command>` element is "restore", this element **MUST NOT** be included; otherwise, it **MUST** be included. If no `<fee:period>` appeared in the client command (and the command is not "restore"), then the server **MUST** return its default period value.
- Zero or more `<fee:fee>` elements (as described in [Section 3.4](#)).
- Zero or more `<fee:credit>` elements (as described in [Section 3.4](#)).
- An **OPTIONAL** `<fee:reason>` element (as described in [Section 3.9](#)).

If the "avail" attribute of the `<fee:cd>` element is true (1) and if no `<fee:fee>` elements are present in a `<fee:command>` element, this indicates that no fee will be assessed by the server for this command.

If the "avail" attribute of the `<fee:cd>` element is true (1), then the `<fee:command>` element **MUST NOT** contain a `<fee:reason>` element.

Example `<check>` response:

```
S: <?xml version="1.0" encoding="utf-8" standalone="no"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1000">
S:       <msg>Command completed successfully</msg>
S:     </result>
S:     <resData>
S:       <domain:chkData
S:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
S:           <domain:cd>
S:             <domain:name avail="1">example.com</domain:name>
S:           </domain:cd>
S:           <domain:cd>
S:             <domain:name avail="1">example.net</domain:name>
S:           </domain:cd>
S:           <domain:cd>
S:             <domain:name avail="1">example.xyz</domain:name>
S:           </domain:cd>
S:         </domain:chkData>
S:       </resData>
S:       <extension>
S:         <fee:chkData
S:           xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
S:             <fee:currency>USD</fee:currency>
S:             <fee:cd avail="1">
S:               <fee:objID>example.com</fee:objID>
S:               <fee:class>Premium</fee:class>
S:               <fee:command name="create">
S:                 <fee:period unit="y">2</fee:period>
S:               <fee:fee
S:                 description="Registration Fee"
S:                 refundable="1"
S:                 grace-period="P5D">10.00</fee:fee>
S:             </fee:command>
S:             <fee:command name="renew">
S:               <fee:period unit="y">1</fee:period>
S:             <fee:fee
S:               description="Renewal Fee"
S:               refundable="1"
S:               grace-period="P5D">10.00</fee:fee>
S:             </fee:command>
S:             <fee:command name="transfer">
S:               <fee:period unit="y">1</fee:period>
S:             <fee:fee
S:               description="Transfer Fee"
S:               refundable="1"
S:               grace-period="P5D">10.00</fee:fee>
S:             </fee:command>
S:             <fee:command name="restore">
S:               <fee:fee
S:                 description="Redemption Fee">15.00</fee:fee>
S:             </fee:command>
S:           </fee:cd>
S:         <fee:cd avail="1">
S:           <fee:objID>example.net</fee:objID>
S:           <fee:class>standard</fee:class>
S:           <fee:command name="create" standard="1">
```

```

S:      <fee:period unit="y">2</fee:period>
S:      <fee:fee
S:        description="Registration Fee"
S:        refundable="1"
S:        grace-period="P5D">5.00</fee:fee>
S:    </fee:command>
S:    <fee:command name="renew" standard="1">
S:      <fee:period unit="y">1</fee:period>
S:      <fee:fee
S:        description="Renewal Fee"
S:        refundable="1"
S:        grace-period="P5D">5.00</fee:fee>
S:    </fee:command>
S:    <fee:command name="transfer" standard="1">
S:      <fee:period unit="y">1</fee:period>
S:      <fee:fee
S:        description="Transfer Fee"
S:        refundable="1"
S:        grace-period="P5D">5.00</fee:fee>
S:    </fee:command>
S:    <fee:command name="restore" standard="1">
S:      <fee:fee
S:        description="Redemption Fee">5.00</fee:fee>
S:    </fee:command>
S:  </fee:cd>
S:  <fee:cd avail="0">
S:    <fee:objID>example.xyz</fee:objID>
S:    <fee:command name="create">
S:      <fee:period unit="y">2</fee:period>
S:      <fee:reason>Only 1 year registration periods are
S:        valid.</fee:reason>
S:    </fee:command>
S:  </fee:cd>
S: </fee:chkData>
S: </extension>
S: <trID>
S:   <cLTRID>ABC-12345</cLTRID>
S:   <svTRID>54322-XYZ</svTRID>
S: </trID>
S: </response>
S: </epp>

```

5.1.2. EPP Transfer Query Command

This extension does not add any elements to the EPP <transfer> query command, but it does include elements in the response when the extension is included in the <login> command service extensions.

When the <transfer> query command has been processed successfully, if the client has included the extension in the <login> command service <svcExtension> element, and if the client is authorized by the server to view information about the transfer, then the server **MAY** include in the <extension> section of the EPP response a <fee:trnData> element, which contains the following child elements:

- A <fee:currency> element (as described in [Section 3.2](#)).

- A <fee:period> element (as described in [Section 3.3](#)).
- Zero or more <fee:fee> elements (as described in [Section 3.4](#)) containing the fees that will be charged to the gaining client.
- Zero or more <fee:credit> elements (as described in [Section 3.4](#)) containing the credits that will be refunded to the losing client.

Servers **SHOULD** omit <fee:credit> when returning a response to the gaining client and omit <fee:fee> elements when returning a response to the losing client.

If no <fee:trnData> element is included in the response, then no fee will be assessed by the server for the transfer.

Example <transfer> query response:

```
S: <?xml version="1.0" encoding="utf-8" standalone="no"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1001">
S:       <msg>Command completed successfully; action pending</msg>
S:     </result>
S:     <resData>
S:       <domain:trnData
S:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
S:         <domain:name>example.com</domain:name>
S:         <domain:trStatus>pending</domain:trStatus>
S:         <domain:reID>ClientX</domain:reID>
S:         <domain:reDate>2019-06-08T22:00:00.0Z</domain:reDate>
S:         <domain:acID>ClientY</domain:acID>
S:         <domain:acDate>2019-06-13T22:00:00.0Z</domain:acDate>
S:         <domain:exDate>2021-09-08T22:00:00.0Z</domain:exDate>
S:       </domain:trnData>
S:     </resData>
S:     <extension>
S:       <fee:trnData xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
S:         <fee:currency>USD</fee:currency>
S:         <fee:period unit="y">1</fee:period>
S:         <fee:fee>5.00</fee:fee>
S:       </fee:trnData>
S:     </extension>
S:     <trID>
S:       <clTRID>ABC-12345</clTRID>
S:       <svTRID>54322-XYZ</svTRID>
S:     </trID>
S:   </response>
S: </epp>
```

5.2. EPP Transform Commands

5.2.1. EPP <create> Command

This extension adds elements to both the EPP <create> command and response when the extension is included in the <login> command service extensions.

When submitting a <create> command to the server, the client **MAY** include in the <extension> element a <fee:create> element, which includes the following child elements:

- An **OPTIONAL** <fee:currency> element (as described in [Section 3.2](#)).
- One or more <fee:fee> elements (as described in [Section 3.4](#)).

When the <create> command has been processed successfully, the client included the extension in the <login> command service extensions, and a fee was assessed by the server for the transaction, the server **MUST** include in the <extension> section of the EPP response a <fee:creData> element, which contains the following child elements:

- A <fee:currency> element (as described in [Section 3.2](#)).
- Zero or more <fee:fee> elements (as described in [Section 3.4](#)).
- Zero or more <fee:credit> elements (as described in [Section 3.4](#)).
- An **OPTIONAL** <fee:balance> element (as described in [Section 3.5](#)).
- An **OPTIONAL** <fee:creditLimit> element (as described in [Section 3.6](#)).

Example <create> command:

```
C: <?xml version="1.0" encoding="utf-8" standalone="no"?>
C: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
C:   <command>
C:     <create>
C:       <domain:create
C:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
C:         <domain:name>example.com</domain:name>
C:         <domain:period unit="y">2</domain:period>
C:         <domain:ns>
C:           <domain:hostObj>ns1.example.net</domain:hostObj>
C:           <domain:hostObj>ns2.example.net</domain:hostObj>
C:         </domain:ns>
C:         <domain:registrant>jd1234</domain:registrant>
C:         <domain:contact type="admin">sh8013</domain:contact>
C:         <domain:contact type="tech">sh8013</domain:contact>
C:         <domain:authInfo>
C:           <domain:pw>2fooBAR</domain:pw>
C:         </domain:authInfo>
C:       </domain:create>
C:     </create>
C:     <extension>
C:       <fee:create xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
C:         <fee:currency>USD</fee:currency>
C:         <fee:fee>5.00</fee:fee>
C:       </fee:create>
C:     </extension>
C:     <clTRID>ABC-12345</clTRID>
C:   </command>
C: </epp>
```

Example <create> response:


```

S: <?xml version="1.0" encoding="utf-8" standalone="no"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1000">
S:       <msg>Command completed successfully</msg>
S:     </result>
S:     <resData>
S:       <domain:creData
S:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
S:         <domain:name>example.com</domain:name>
S:         <domain:crDate>2019-04-03T22:00:00.0Z</domain:crDate>
S:         <domain:exDate>2021-04-03T22:00:00.0Z</domain:exDate>
S:       </domain:creData>
S:     </resData>
S:     <extension>
S:       <fee:creData xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
S:         <fee:currency>USD</fee:currency>
S:         <fee:fee
S:           description="Registration Fee"
S:           lang="en"
S:           refundable="1"
S:           grace-period="P5D">5.00</fee:fee>
S:         <fee:balance>-5.00</fee:balance>
S:         <fee:creditLimit>1000.00</fee:creditLimit>
S:       </fee:creData>
S:     </extension>
S:     <trID>
S:       <clTRID>ABC-12345</clTRID>
S:       <svTRID>54321-XYZ</svTRID>
S:     </trID>
S:   </response>
S: </epp>

```

5.2.2. EPP <delete> Command

This extension does not add any elements to the EPP <delete> command, but it does include elements in the response when the extension is included in the <login> command service extensions.

When the <delete> command has been processed successfully and the client included the extension in the <login> command service extensions, the server **MAY** include in the <extension> section of the EPP response a <fee:delData> element, which contains the following child elements:

- A <fee:currency> element (as described in [Section 3.2](#)).
- Zero or more <fee:fee> elements (as described in [Section 3.4](#)).
- Zero or more <fee:credit> elements (as described in [Section 3.4](#)).
- An **OPTIONAL** <fee:balance> element (as described in [Section 3.5](#)).
- An **OPTIONAL** <fee:creditLimit> element (as described in [Section 3.6](#)).

Example <delete> response:

```
S: <?xml version="1.0" encoding="utf-8" standalone="no"?>
S: <epp xmlns="urn:iETF:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1000">
S:       <msg>Command completed successfully</msg>
S:     </result>
S:     <extension>
S:       <fee:delData
S:         xmlns:fee="urn:iETF:params:xml:ns:epp:fee-1.0">
S:           <fee:currency>USD</fee:currency>
S:           <fee:credit
S:             description="AGP Credit"
S:             lang="en">-5.00</fee:credit>
S:           <fee:balance>1005.00</fee:balance>
S:         </fee:delData>
S:       </extension>
S:       <trID>
S:         <clTRID>ABC-12345</clTRID>
S:         <svTRID>54321-XYZ</svTRID>
S:       </trID>
S:     </response>
S: </epp>
```

5.2.3. EPP <renew> Command

This extension adds elements to both the EPP <renew> command and response when the extension is included in the <login> command service extensions.

When submitting a <renew> command to the server, the client **MAY** include in the <extension> element a <fee:renew> element, which includes the following child elements:

- An **OPTIONAL** <fee:currency> element (as described in [Section 3.2](#)).
- One or more <fee:fee> elements (as described in [Section 3.4](#)).

When the <renew> command has been processed successfully and the client included the extension in the <login> command service extensions, the server **MAY** include in the <extension> section of the EPP response a <fee:renData> element, which contains the following child elements:

- A <fee:currency> element (as described in [Section 3.2](#)).
- Zero or more <fee:fee> elements (as described in [Section 3.4](#)).
- Zero or more <fee:credit> elements (as described in [Section 3.4](#)).
- An **OPTIONAL** <fee:balance> element (as described in [Section 3.5](#)).
- An **OPTIONAL** <fee:creditLimit> element (as described in [Section 3.6](#)).

Example <renew> command:

```

C: <?xml version="1.0" encoding="utf-8" standalone="no"?>
C: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
C:   <command>
C:     <renew>
C:       <domain:renew
C:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
C:           <domain:name>example.com</domain:name>
C:           <domain:curExpDate>2019-04-03</domain:curExpDate>
C:           <domain:period unit="y">5</domain:period>
C:         </domain:renew>
C:       </renew>
C:     <extension>
C:       <fee:renew xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
C:         <fee:currency>USD</fee:currency>
C:         <fee:fee>5.00</fee:fee>
C:       </fee:renew>
C:     </extension>
C:     <clTRID>ABC-12345</clTRID>
C:   </command>
C: </epp>

```

Example <renew> response:

```

S: <?xml version="1.0" encoding="utf-8" standalone="no"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1000">
S:       <msg>Command completed successfully</msg>
S:     </result>
S:     <resData>
S:       <domain:renData
S:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
S:           <domain:name>example.com</domain:name>
S:           <domain:exDate>2024-04-03T22:00:00.0Z</domain:exDate>
S:         </domain:renData>
S:       </resData>
S:     <extension>
S:       <fee:renData xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
S:         <fee:currency>USD</fee:currency>
S:         <fee:fee
S:           refundable="1"
S:           grace-period="P5D">5.00</fee:fee>
S:         <fee:balance>1000.00</fee:balance>
S:       </fee:renData>
S:     </extension>
S:     <trID>
S:       <clTRID>ABC-12345</clTRID>
S:       <svTRID>54322-XYZ</svTRID>
S:     </trID>
S:   </response>
S: </epp>

```

5.2.4. EPP <transfer> Command

This extension adds elements to both the EPP <transfer> command and response when the value of the "op" attribute of the <transfer> command element is "request" and the extension is included in the <login> command service extensions.

When submitting a <transfer> command to the server, the client **MAY** include in the <extension> element a <fee:transfer> element, which includes the following child elements:

- An **OPTIONAL** <fee:currency> element (as described in [Section 3.2](#)).
- One or more <fee:fee> elements (as described in [Section 3.4](#)).

When the <transfer> command has been processed successfully and the client included the extension in the <login> command service extensions, the server **MAY** include in the <extension> section of the EPP response a <fee:trnData> element, which contains the following child elements:

- A <fee:currency> element (as described in [Section 3.2](#)).
- Zero or more <fee:fee> elements (as described in [Section 3.4](#)).
- Zero or more <fee:credit> elements (as described in [Section 3.4](#)).
- An **OPTIONAL** <fee:balance> element (as described in [Section 3.5](#)).
- An **OPTIONAL** <fee:creditLimit> element (as described in [Section 3.6](#)).

Example <transfer> command:

```
C: <?xml version="1.0" encoding="utf-8" standalone="no"?>
C: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
C:   <command>
C:     <transfer op="request">
C:       <domain:transfer
C:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
C:         <domain:name>example.com</domain:name>
C:         <domain:period unit="y">1</domain:period>
C:         <domain:authInfo>
C:           <domain:pw roid="JD1234-REP">2fooBAR</domain:pw>
C:         </domain:authInfo>
C:       </domain:transfer>
C:     </transfer>
C:     <extension>
C:       <fee:transfer xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
C:         <fee:currency>USD</fee:currency>
C:         <fee:fee>5.00</fee:fee>
C:       </fee:transfer>
C:     </extension>
C:     <cLTRID>ABC-12345</cLTRID>
C:   </command>
C: </epp>
```

Example <transfer> response:

```

S: <?xml version="1.0" encoding="utf-8" standalone="no"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1001">
S:       <msg>Command completed successfully; action pending</msg>
S:     </result>
S:     <resData>
S:       <domain:trnData
S:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
S:         <domain:name>example.com</domain:name>
S:         <domain:trStatus>pending</domain:trStatus>
S:         <domain:reID>ClientX</domain:reID>
S:         <domain:reDate>2019-06-08T22:00:00.0Z</domain:reDate>
S:         <domain:acID>ClientY</domain:acID>
S:         <domain:acDate>2019-06-13T22:00:00.0Z</domain:acDate>
S:         <domain:exDate>2021-09-08T22:00:00.0Z</domain:exDate>
S:       </domain:trnData>
S:     </resData>
S:     <extension>
S:       <fee:trnData xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
S:         <fee:currency>USD</fee:currency>
S:         <fee:fee
S:           refundable="1"
S:           grace-period="P5D">5.00</fee:fee>
S:       </fee:trnData>
S:     </extension>
S:     <trID>
S:       <clTRID>ABC-12345</clTRID>
S:       <svTRID>54322-XYZ</svTRID>
S:     </trID>
S:   </response>
S: </epp>

```

5.2.5. EPP <update> Command

This extension adds elements to both the EPP <update> command and response when the extension is included in the <login> command service extensions.

When submitting an <update> command to the server, the client **MAY** include in the <extension> element a <fee:update> element, which includes the following child elements:

- An **OPTIONAL** <fee:currency> element (as described in [Section 3.2](#)).
- One or more <fee:fee> elements (as described in [Section 3.4](#)).

When the <update> command has been processed successfully and the client included the extension in the <login> command service extensions, the server **MAY** include in the <extension> section of the EPP response a <fee:updData> element, which contains the following child elements:

- A <fee:currency> element (as described in [Section 3.2](#)).
- Zero or more <fee:fee> elements (as described in [Section 3.4](#)).
- Zero or more <fee:credit> elements (as described in [Section 3.4](#)).

- An **OPTIONAL** <fee:balance> element (as described in [Section 3.5](#)).
- An **OPTIONAL** <fee:creditLimit> element (as described in [Section 3.6](#)).

Example <update> command:

```
C: <?xml version="1.0" encoding="utf-8" standalone="no"?>
C: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
C:   <command>
C:     <update>
C:       <domain:update>
C:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
C:           <domain:name>example.com</domain:name>
C:           <domain:chg>
C:             <domain:registrant>sh8013</domain:registrant>
C:           </domain:chg>
C:         </domain:update>
C:       </update>
C:     <extension>
C:       <fee:update xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
C:         <fee:currency>USD</fee:currency>
C:         <fee:fee>5.00</fee:fee>
C:       </fee:update>
C:     </extension>
C:     <clTRID>ABC-12345</clTRID>
C:   </command>
C: </epp>
```

Example <update> response:

```
S: <?xml version="1.0" encoding="utf-8" standalone="no"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
S:   <response>
S:     <result code="1000">
S:       <msg>Command completed successfully</msg>
S:     </result>
S:     <extension>
S:       <fee:updData xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0">
S:         <fee:currency>USD</fee:currency>
S:         <fee:fee>5.00</fee:fee>
S:       </fee:updData>
S:     </extension>
S:     <trID>
S:       <clTRID>ABC-12345</clTRID>
S:       <svTRID>54321-XYZ</svTRID>
S:     </trID>
S:   </response>
S: </epp>
```

6. Formal Syntax

One schema is presented here -- the EPP Fee Extension schema.

The formal syntax presented here is a complete schema representation of the object mapping suitable for automated validation of EPP XML instances.

6.1. Fee Extension Schema

The formal syntax presented here is a complete schema representation [[W3C.REC-xmlschema-1-20041028](#)] of the object mapping suitable for automated validation of EPP XML instances. The <CODE BEGINS> and <CODE ENDS> tags are not part of the schema; they are used to note the beginning and end of the schema for URI registration purposes.

```
<CODE BEGINS>
<?xml version="1.0" encoding="utf-8"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  xmlns:fee="urn:ietf:params:xml:ns:epp:fee-1.0"
  xmlns:eppcom="urn:ietf:params:xml:ns:eppcom-1.0"
  xmlns:domain="urn:ietf:params:xml:ns:domain-1.0"
  targetNamespace="urn:ietf:params:xml:ns:epp:fee-1.0"
  elementFormDefault="qualified">

  <import namespace="urn:ietf:params:xml:ns:eppcom-1.0" />
  <import namespace="urn:ietf:params:xml:ns:domain-1.0" />

  <annotation>
    <documentation>
      Extensible Provisioning Protocol v1.0 Fee Extension
    </documentation>
  </annotation>

  <!-- Child elements found in EPP commands and responses -->
  <element name="check" type="fee:checkType" />
  <element name="chkData" type="fee:chkDataType" />
  <element name="create" type="fee:transformCommandType" />
  <element name="creData" type="fee:transformResultType" />
  <element name="renew" type="fee:transformCommandType" />
  <element name="renData" type="fee:transformResultType" />
  <element name="transfer" type="fee:transformCommandType" />
  <element name="trnData" type="fee:transformResultType" />
  <element name="update" type="fee:transformCommandType" />
  <element name="updData" type="fee:transformResultType" />
  <element name="delData" type="fee:transformResultType" />

  <!-- client <check> command -->
  <complexType name="checkType">
    <sequence>
      <element name="currency" type="fee:currencyType"
        minOccurs="0" />
      <element name="command" type="fee:commandType"
        minOccurs="1" maxOccurs="unbounded" />
    </sequence>
  </complexType>

  <complexType name="objectIdentifierType">
    <simpleContent>
      <extension base="eppcom:labelType">
        <attribute name="element"
          type="NMTOKEN" default="name" />
      </extension>
    </simpleContent>
  </complexType>

  <!-- server <check> result -->
  <complexType name="chkDataType">
    <sequence>
      <element name="currency" type="fee:currencyType" />
      <element name="cd" type="fee:objectCDType"
        maxOccurs="unbounded" />
    </sequence>
  </complexType>
```



```
</complexType>

<complexType name="objectCDType">
  <sequence>
    <element name="objID" type="fee:objectIdentifierType" />
    <element name="class" type="token" minOccurs="0" />
    <element name="command" type="fee:commandDataType"
      minOccurs="0" maxOccurs="unbounded" />
    <element name="reason" type="fee:reasonType" minOccurs="0" />
  </sequence>
  <attribute name="avail" type="boolean" default="1" />
</complexType>

<!-- general transform (create, renew, update, transfer) command-->
<complexType name="transformCommandType">
  <sequence>
    <element name="currency" type="fee:currencyType"
      minOccurs="0" />
    <element name="fee" type="fee:feeType"
      maxOccurs="unbounded" />
    <element name="credit" type="fee:creditType"
      minOccurs="0" maxOccurs="unbounded" />
  </sequence>
</complexType>

<!-- general transform (create, renew, update) result -->
<complexType name="transformResultType">
  <sequence>
    <element name="currency" type="fee:currencyType"
      minOccurs="0" />
    <element name="period" type="domain:periodType"
      minOccurs="0" />
    <element name="fee" type="fee:feeType"
      minOccurs="0" maxOccurs="unbounded" />
    <element name="credit" type="fee:creditType"
      minOccurs="0" maxOccurs="unbounded" />
    <element name="balance" type="fee:balanceType"
      minOccurs="0" />
    <element name="creditLimit" type="fee:creditLimitType"
      minOccurs="0" />
  </sequence>
</complexType>

<!-- common types -->
<simpleType name="currencyType">
  <restriction base="string">
    <pattern value="[A-Z]{3}" />
  </restriction>
</simpleType>

<complexType name="commandType">
  <sequence>
    <element name="period" type="domain:periodType"
      minOccurs="0" maxOccurs="1" />
  </sequence>
  <attribute name="name" type="fee:commandEnum" use="required"/>
  <attribute name="customName" type="token"/>
  <attribute name="phase" type="token" />

```

```
<attribute name="subphase" type="token" />
</complexType>

<complexType name="commandDataType">
  <complexContent>
    <extension base="fee:commandType">
      <sequence>
        <element name="fee" type="fee:feeType"
          minOccurs="0" maxOccurs="unbounded" />
        <element name="credit" type="fee:creditType"
          minOccurs="0" maxOccurs="unbounded" />
        <element name="reason" type="fee:reasonType"
          minOccurs="0" />
      </sequence>
      <attribute name="standard" type="boolean" default="0" />
    </extension>
  </complexContent>
</complexType>

<complexType name="reasonType">
  <simpleContent>
    <extension base="token">
      <attribute name="lang" type="language" default="en"/>
    </extension>
  </simpleContent>
</complexType>

<simpleType name="commandEnum">
  <restriction base="token">
    <enumeration value="create"/>
    <enumeration value="delete"/>
    <enumeration value="renew"/>
    <enumeration value="update"/>
    <enumeration value="transfer"/>
    <enumeration value="restore"/>
    <enumeration value="custom"/>
  </restriction>
</simpleType>

<simpleType name="nonNegativeDecimal">
  <restriction base="decimal">
    <minInclusive value="0" />
  </restriction>
</simpleType>

<simpleType name="negativeDecimal">
  <restriction base="decimal">
    <maxInclusive value="0" />
  </restriction>
</simpleType>

<complexType name="feeType">
  <simpleContent>
    <extension base="fee:nonNegativeDecimal">
      <attribute name="description"/>
      <attribute name="lang" type="language" default="en"/>
      <attribute name="refundable" type="boolean" />
      <attribute name="grace-period" type="duration" />
    </extension>
  </simpleContent>
</complexType>
```

```
<attribute name="applied">
  <simpleType>
    <restriction base="token">
      <enumeration value="immediate" />
      <enumeration value="delayed" />
    </restriction>
  </simpleType>
</attribute>
</extension>
</simpleContent>
</complexType>

<complexType name="creditType">
  <simpleContent>
    <extension base="fee:negativeDecimal">
      <attribute name="description"/>
      <attribute name="lang" type="language" default="en"/>
    </extension>
  </simpleContent>
</complexType>

<simpleType name="balanceType">
  <restriction base="decimal" />
</simpleType>

<simpleType name="creditLimitType">
  <restriction base="decimal" />
</simpleType>

</schema>

<CODE ENDS>
```

7. Security Considerations

The mapping extensions described in this document do not provide any security services beyond those described by the EPP [RFC5730], the EPP domain name mapping [RFC5731], and the protocol layers used by the EPP. The security considerations described in these other specifications apply to this specification as well. This extension passes financial information using the EPP protocol, so confidentiality and integrity protection must be provided by the transport mechanism. All transports compliant with [RFC5730] provide the needed level of confidentiality and integrity protections. The server will only provide information, including financial information, that is relevant to the authenticated client.

8. IANA Considerations

8.1. XML Namespace

This document uses URNs to describe XML namespaces and XML schemas conforming to a registry mechanism described in [RFC3688].

Registration request for the fee namespace:

URI: urn:ietf:params:xml:ns:epp:fee-1.0

Registrant Contact: IESG

XML: None. Namespace URIs do not represent an XML specification.

Registration request for the fee schema:

URI: urn:ietf:params:xml:schema:epp:fee-1.0

Registrant Contact: IESG

XML: See [Section 6](#) of this document.

8.2. EPP Extension Registry

The EPP extension described in this document has been registered by IANA in the "Extensions for the Extensible Provisioning Protocol (EPP)" registry described in [\[RFC7451\]](#). The details of the registration are as follows:

Name of Extension: Registry Fee Extension for the Extensible Provisioning Protocol (EPP)

Document status: Standards Track

Reference: RFC 8748

Registrant Name and Email Address: IESG <iesg@ietf.org>

TLDs: Any

IPR Disclosure: None

Status: Active

Notes: None

9. References

9.1. Normative References

[ISO4217_2015] ISO, "Codes for the representation of currencies", ISO 4217:2015, August 2015, <<https://www.iso.org/standard/64758.html>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

- [RFC3915] Hollenbeck, S., "Domain Registry Grace Period Mapping for the Extensible Provisioning Protocol (EPP)", RFC 3915, DOI 10.17487/RFC3915, September 2004, <<https://www.rfc-editor.org/info/rfc3915>>.
- [RFC5646] Phillips, A., Ed. and M. Davis, Ed., "Tags for Identifying Languages", BCP 47, RFC 5646, DOI 10.17487/RFC5646, September 2009, <<https://www.rfc-editor.org/info/rfc5646>>.
- [RFC5730] Hollenbeck, S., "Extensible Provisioning Protocol (EPP)", STD 69, RFC 5730, DOI 10.17487/RFC5730, August 2009, <<https://www.rfc-editor.org/info/rfc5730>>.
- [RFC5731] Hollenbeck, S., "Extensible Provisioning Protocol (EPP) Domain Name Mapping", STD 69, RFC 5731, DOI 10.17487/RFC5731, August 2009, <<https://www.rfc-editor.org/info/rfc5731>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8334] Gould, J., Tan, W., and G. Brown, "Launch Phase Mapping for the Extensible Provisioning Protocol (EPP)", RFC 8334, DOI 10.17487/RFC8334, March 2018, <<https://www.rfc-editor.org/info/rfc8334>>.
- [W3C.REC-xmlschema-1-20041028] Thompson, H., Beech, D., Maloney, M., and N. Mendelsohn, "XML Schema Part 1: Structures Second Edition", World Wide Web Consortium Recommendation REC-xmlschema-1-20041028, October 2004, <<http://www.w3.org/TR/2004/REC-xmlschema-1-20041028>>.

9.2. Informative References

- [RFC7451] Hollenbeck, S., "Extension Registry for the Extensible Provisioning Protocol", RFC 7451, DOI 10.17487/RFC7451, February 2015, <<https://www.rfc-editor.org/info/rfc7451>>.

Acknowledgements

The authors wish to thank the following persons for their feedback and suggestions:

- James Gould of Verisign Inc.
- Luis Munoz of ISC
- Michael Young
- Ben Levac
- Jeff Eckhaus
- Seth Goldman of Google

- Klaus Malorny and Michael Bauland of Knipp
- Jody Kolker, Joe Snitker, and Kevin Allendorf of GoDaddy
- Michael Holloway of Com Laude
- Santosh Kalsangrah of Impetus Infotech
- Alex Mayrhofer of Nic.at
- Thomas Corte of Knipp Medien und Kommunikation GmbH

Authors' Addresses

Roger Carney

GoDaddy Inc.

14455 N. Hayden Rd. #219

Scottsdale, AZ 85260

United States of America

Email: rcarney@godaddy.com

URI: <http://www.godaddy.com>

Gavin Brown

CentralNic Group plc

35-39 Moorgate

London

EC2R 6AR

United Kingdom

Phone: [+44 20 33 88 0600](tel:+442033880600)

Email: gavin.brown@centralnic.com

URI: <http://www.centralnic.com>

Jothan Frakes

Email: jothan@jothan.com

URI: <http://jothan.com>